

The First and The Foremost Choice



Authorised Dealer



Engineering For The Future



An ISO 9001 - 2015 Certified Company

www.activeseals.com



2/2 Diaphragm Valve

Orifice : 10 mm to 50 mm
Pressure : Up to 20 Bar
BarSpeed : Up to 100 cycles / min.
Media : Air, Inert gases, water,
 free flowing liquid



2/2 & 3/2 Direct Acting Valve

Orifice : Up to 10 mm
Pressure : Up to 400 Bar
Speed : Up to 1000 cycles / min
Media : Air, Inert gases, water,
 vacuum, free flowing liquid



2/2 Pulse Jet Valve / Dust Collector Valve

Size : 3/4" to 3"
Pressure : 8.5 Bar / 16 Bar



5/2 Pilot Operated Poppet Valve

Orifice : 6mm to 50 mm
Pressure : Up to 70 Bar
Speed : Up to 1000 cycles / min
Media : Air, Inert gases, water,
 vacuum, free flowing liquid



5/2 Spool Valve

Orifice : 4 mm to 10 mm
Pressure : Up to 10 Bar
Speed : Up to 1000 cycles / min
Media : Air



Namur Valve

3/2 and 5/2 - 3/2, convertible solenoid valve for Single / Double acting rotary actuator. Working Pressure : Up to 20 Bar



2/2 Piston Operated Solenoid Valve

Orifice : 12, 20, 25, 40, 50, 65 mm
Pressure : Up To 40 Bar



Actuator

Double Rack and Pinion Actuator
 Single / Double Acting
 Hard Anodized body providing high corrosion resistance



Air, Lever, Push Button Operated Valve

3/2, 5/2 and 5/3 hand operated, hand / spring return valve
Orifice : 3 mm to 10 mm



Angle Seat Valve

Size : 1/2" to 3"
 All wetted parts SS 316L
 Wide range of operators from dia 40mm to 110 mm



Pneumatics Cylinder

Dia 8 to 25mm As par ISO 6432 & CETOP RP 52P
 Dia 32 to 160 mm As par ISO 15552 and VDMA 24562
 Single / Double Acting
 Stroke up to 3000 mm



Pneumatics Push In Fittings

All type of Pneumatics Push In Fittings



Brass Fittings

All type of Brass Fittings



SS Fittings

All type of SS Fittings



Limit Switch

Aluminium Diecast with powder coating for superior corrosion resistance
Weather Proof / Explosion Proof Options Available.



Positioner

Pneumatics / Electro Pneumatics
Options Available
Compact Design , Rugged Construction with rigid ISO 5211 Mounting
All the internal Parts are hard anodized



Pressure Gauge

Dial Size : DN 40 To DN 250
Range : -1 to 1600 Bar
Mounting Style : All type of standard mounting style available



Temperature Gauge

Dial Size : DN 50 To DN 250
Range : -100 to 650 deg. C
Mounting Style : All type of standard mounting style available



Butterfly Valve

Size : DN 50 to DN 600
Pressure Range : PN 3.5, PN 6, PN 10, PN 16
MOC : Various Variety of Body MOC with manual and Automation. ISO Pad for mounting Hand Lever / Gear Operated / Actuator Easily serviceable at customer end



Ball Valve

Size : DN 15 mm to DN 200 mm
Seat : Special TFM 1600 Grade Seat
Ball : Large & Mirror Finished SS Ball
MOC : Various Variety of Body MOC with manual and Automation



Power Cylinder

Various type of Power Cylinder with positioners and manual override



Pressure Transmitter

Pressure Range : 0 to 600 Bar
Design For use in Severe Industrial Environment Enclosure and Wetted Parts of acid resistance SS (AISI 316 L)



Electrical Actuator Operated Valve

Type : Ball / Butterfly / Globe
Size : As Par Customer's requirement
MOC : Various Variety Of MOC With Feedback Provision



RTD & Thermocouple

Type : Simplex / Duplex / J / K
Stem Dia : 6mm / 8mm / 10mm
End Connection : As par customer's requirement



PU Tubing

All standard size and colours



Pressure Switch

Wide Regulating Range. Can be used for Pump, Turbine, Fire Fighting System, Boiler & Compressor. Compact & Economical. Auto Reset



Intrinsically Safe Solenoid Valve Plug In Enclosure

- 3/2, 5/2 Valve
- Working Pressure Up to 8 Bar
- Suitable For Zone 1 Remote i / o



Intrinsically Solenoid Valve Ex D Enclosure

- 3/2 and 5/2 valve with dual protection i.e. low power solenoid housed in Ex d enclosure.
- Working Pressure Up to 8 Bar
- Suitable For Zone 1 Remote i / o



Latch Solenoid Valve

- 2/2, 3/2, 5/2 valve with Latch solenoid for valve to work as power fail to stayput type (LC)
- Working Pressure Up to 20 Bar



Low Power Solenoid Valve

- 2/2, 3/2 and 5/2 valve operated with 5 W, 2 W, 0.4 W Solenoid
- Working Pressure Up to 16 Bar



NISHAKA PNEUMATICS



IMI NORGREN®

Authorised Dealer



Engineering For The Future

For advanced drive technology



KTR
Kupplungstechnik GmbH
Germany



An ISO 9001 - 2015 Certified Company

Mfg. : Industrial Pumps, Mechanical Seals, Pump Spares and Industrial Goods

Plot No. 69/3, Shed No. C-2/A-3, Near Torrento Ghar Ghanti, Phase-I, 'C' Road, G.I.D.C. Vatva, Ahmedabad - 382445. (Gujarat) INDIA. Phone : +91-79-25897244, 7600040040, E-mail : info@activeseals.com, sales@activeseals.com, active_eng2002@yahoo.com, Website: www.activeseals.com

Surat Office :

F-51, Silicon Shoppers, Near South Zone Office, Udhna Main Road, Udhna, Surat - 394210 (Gujarat) INDIA. E-mail : marketing@activeseals.com, Mobile: +91-7600052072 / 7600052073